



Issue date 12-Mar-2015

# Safety Data Sheet

Version 1

## 1. Identification of the Substance/Preparation and of the Company/Undertaking

### Product Identifier

**Product name** SPRAYPAK VANDAL MARK REMOVER  
**Chemical name** 7-7785-3

### Other means of identification

**Product code** FG 433-4105-8  
**Synonyms** Graffiti Remover

### Recommended use of the chemical and restrictions on use

**Recommended Use** Vandal mark remover.  
**Uses advised against** Do not use to clean glass or wood surfaces. DO NOT USE ON FLOORS

### Details of the supplier of the safety data sheet

**Supplier Address**  
Chase Products Co.  
2727 Gardner Road  
Broadview, IL 60155  
708-273-1121

**Manufacturer Address**  
Chase Products Co.  
2727 Gardner Road  
Broadview, IL 60155  
708-273-1121

**Emergency Telephone Number**  
**Company Phone Number** 708-865-1000  
**24 Hour Emergency Phone Number** 1-800-255-3924  
**Emergency telephone** ChemTel 1-800-255-3924

## 2. Hazards Identification

### Classification

Acute toxicity - Inhalation (Gases)	Category 3
Acute toxicity - Inhalation (Vapors)	Category 4
Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Skin sensitization	Category 1
Germ Cell Mutagenicity	Category 1B
carcinogenicity	Category 1B
Reproductive Toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Aspiration toxicity	Category 1
FLAMMABLE AEROSOLS	Category 1
Gases Under Pressure	liquefied gas

### Label Elements

#### EMERGENCY OVERVIEW

**DANGER**

#### **hazard statements**

Toxic if inhaled  
CAUSES SKIN IRRITATION  
Causes serious eye irritation  
May cause an allergic skin reaction  
May cause genetic defects

## FG 433-4105-8 SPRAYPAK VANDAL MARK REMOVER

May cause cancer  
Suspected of damaging fertility or the unborn child  
May cause respiratory irritation. May cause drowsiness or dizziness  
May cause damage to organs through prolonged or repeated exposure  
May be fatal if swallowed and enters airways  
EXTREMELY FLAMMABLE AEROSOL  
Pressurized container: May burst if heated  
Contains gas under pressure; may explode if heated



**Appearance** Dark yellow to light green liquid

**Physical State** Aerosol

**Odor** Petroleum distillates

### Precautionary Statements - Prevention

Obtain special instructions before use  
Do not handle until all safety precautions have been read and understood  
Do not eat, drink or smoke when using this product  
Use personal protective equipment as required  
Wear protective gloves, protective clothing, eye protection and face protection.  
Use only outdoors or in a well-ventilated area  
Wash face, hands and any exposed skin thoroughly after handling  
Contaminated work clothing should not be allowed out of the workplace  
Do not breathe fumes, mist, vapors or spray.  
Keep away from heat, sparks, open flames and hot surfaces. — No smoking  
Pressurized container: Do not pierce or burn, even after use  
Do not spray on an open flame or other ignition source

### Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention  
Specific treatment: See additional cautionary statements on this label.  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
If eye irritation persists: Get medical advice/attention  
IF ON SKIN: Wash with plenty of soap and water  
Take off contaminated clothing and wash before reuse  
If skin irritation or rash occurs: Get medical advice/attention  
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
Call a POISON CENTER or doctor/physician  
IF SWALLOWED: Immediately call a POISON CENTER or doctor.  
Do NOT induce vomiting

### Precautionary Statements - Storage

Store locked up  
Store in a well-ventilated place. Keep container tightly closed  
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

### Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

### Hazards not otherwise classified (HNOC)

#### Other Information

- Harmful to aquatic life with long lasting effects
- MAY BE HARMFUL IF SWALLOWED
- May be harmful in contact with skin
- Toxic to aquatic life with long lasting effects

### 3. Composition/information on Ingredients

**Synonyms** Graffiti Remover.  
**Chemical Family** MIXTURES.  
**Formula** 7-7785-3

Chemical name	CAS No	weight-%	Trade secret
Acetone	67-64-1	20-25	*
Dimethyl Glutarate	1119-40-0	10-15	*
Petroleum naphtha, light aromatic	64742-95-6	10-15	*
Propane	74-98-6	5-10	*
Toluene	108-88-3	5-10	*
N-Butane	106-97-8	5-10	*
1,2,4 Trimethylbenzene	95-63-6	5-10	*
Propylene carbonate	108-32-7	1-5	*
Ethyl alcohol	64-17-5	1-5	*
Pine Oil	8002-09-3	1-5	*
D-Limonene	5989-27-5	1-5	*
Diacetone alcohol	123-42-2	1-5	*
Cocamide diethanolamine	68603-42-9	1-2	*
Cumene	98-82-8	<1	*

\* The exact percentage (concentration) of composition has been withheld as a trade secret.

### 4. First aid measures

#### FIRST AID MEASURES

**Eye Contact** Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control center or doctor for treatment advice.

**Skin contact** Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control center or doctor for treatment advise.

**inhalation** If overcome by vapor, move person to fresh air. If person is not breathing, call 911 or an ambulance, then provide artificial respiration, preferably mouth-to-mouth, if possible. Call a poison control center or doctor for further treatment advise.

**INGESTION** Call a poison control center or doctor for treatment advice. Have person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by a poison control center or doctor. Do not give anything by mouth to an unconscious person.

#### Most important symptoms and effects, both acute and delayed

**Symptoms** Acute: Prolonged inhalation of concentrated vapor or mist may cause headaches, dizziness and nausea. Prolonged and repeated contact with skin may cause irritation and reddening. Contact with eyes causes irritation.

#### Indication of any immediate medical attention and special treatment needed

**Note to physicians** Contains petroleum distillates, do not induce vomiting because of aspiration pneumonia hazard.

### 5. Fire-fighting measures

#### Suitable extinguishing media

Dry chemical, CO2 or water spray.

**Unsuitable extinguishing media** Caution: Use of water spray when fighting fire may be inefficient.

**Specific hazards arising from the chemical**

This product is under pressure. Water spray may be used to cool cans in the vicinity of fire or excessive heat to prevent the explosion of the cans.

**Hazardous combustion products** Thermal decomposition may yield gases like nitrogen oxides, carbon monoxide and carbon dioxide.

**Explosion data**

**Sensitivity to Mechanical Impact** Contents under pressure. This product is extremely flammable. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity).

**Sensitivity to Static Discharge** Keep away from heat, sparks, flame, and other sources of ignition (i.e., pilot lights, electric motors and static electricity).

**Protective equipment and precautions for firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

**6. Accidental release measures**

**Personal precautions, protective equipment and emergency procedures**

**Personal precautions** Use in well-ventilated area ONLY. NOTICE: Reports have associated repeated and prolonged occupational over exposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. To avoid breathing vapor or spray mist open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air or wear an appropriate, properly fitted respirator (NIOSH approved), or leave the area. NOTE: Follow respirator manufacturer's instructions carefully for respirator use.

**For emergency responders** Remove all sources of ignition.

**Environmental Precautions**

**Environmental Precautions** See Section 12 for additional Ecological Information.

**Methods and material for containment and cleaning up**

**Methods for Containment** Provide adequate ventilation to area being treated. Soak up spills with chemically inert, absorbent material.

**Methods for cleaning up** Clean contaminated surface thoroughly.

**7. Handling and Storage**

**Precautions for safe handling**

**Advice on safe handling** Handle as an extremely flammable material. Avoid contact with skin, eyes and clothing. Store cans in a cool, dry place away from heat and open flame.

**Conditions for safe storage, including any incompatibilities**

**Storage Conditions** Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). **AEROSOL STORAGE LEVEL III (NFPA-30B).**

**Incompatible Materials** Avoid heat, open flame and contact with strong acids, strong bases and strong oxidizers.

**8. Exposure Controls/Personal Protection**

## FG 433-4105-8 SPRAYPAK VANDAL MARK REMOVER

### Control parameters

#### Exposure guidelines

See occupational exposure limits listed below.

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Acetone 67-64-1	STEL: 750 ppm TWA: 500 ppm	TWA: 1000 ppm TWA: 2400 mg/m <sup>3</sup> (vacated) TWA: 750 ppm (vacated) TWA: 1800 mg/m <sup>3</sup> (vacated) STEL: 2400 mg/m <sup>3</sup> The acetone STEL does not apply to the cellulose acetate fiber industry. It is in effect for all other sectors (vacated) STEL: 1000 ppm	IDLH: 2500 ppm TWA: 250 ppm TWA: 590 mg/m <sup>3</sup>
Propane 74-98-6	TWA: 1000 ppm	TWA: 1000 ppm TWA: 1800 mg/m <sup>3</sup> (vacated) TWA: 1000 ppm (vacated) TWA: 1800 mg/m <sup>3</sup>	IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m <sup>3</sup>
Toluene 108-88-3	TWA: 20 ppm	TWA: 200 ppm (vacated) TWA: 100 ppm (vacated) TWA: 375 mg/m <sup>3</sup> (vacated) STEL: 150 ppm (vacated) STEL: 560 mg/m <sup>3</sup> Ceiling: 300 ppm	IDLH: 500 ppm TWA: 100 ppm TWA: 375 mg/m <sup>3</sup> STEL: 150 ppm STEL: 560 mg/m <sup>3</sup>
N-Butane 106-97-8	STEL: 1000 ppm	(vacated) TWA: 800 ppm (vacated) TWA: 1900 mg/m <sup>3</sup>	TWA: 800 ppm TWA: 1900 mg/m <sup>3</sup>
1,2,4 Trimethylbenzene 95-63-6	-	-	TWA: 25 ppm TWA: 125 mg/m <sup>3</sup>
Ethyl alcohol 64-17-5	STEL: 1000 ppm	TWA: 1000 ppm TWA: 1900 mg/m <sup>3</sup> (vacated) TWA: 1000 ppm (vacated) TWA: 1900 mg/m <sup>3</sup>	IDLH: 3300 ppm TWA: 1000 ppm TWA: 1900 mg/m <sup>3</sup>
Diacetone alcohol 123-42-2	TWA: 50 ppm	TWA: 50 ppm TWA: 240 mg/m <sup>3</sup> (vacated) TWA: 50 ppm (vacated) TWA: 240 mg/m <sup>3</sup>	IDLH: 1800 ppm TWA: 50 ppm TWA: 240 mg/m <sup>3</sup>
Cumene 98-82-8	TWA: 50 ppm	TWA: 50 ppm TWA: 245 mg/m <sup>3</sup> (vacated) TWA: 50 ppm (vacated) TWA: 245 mg/m <sup>3</sup> (vacated) S* S*	IDLH: 900 ppm TWA: 50 ppm TWA: 245 mg/m <sup>3</sup>

### Appropriate engineering controls

#### Engineering controls

Use with adequate general or local exhaust ventilation.

### Individual protection measures, such as personal protective equipment

#### Eye/face Protection

Conventional eyeglasses to guard against splashing.

#### Skin and Body Protection

Chemical resistant gloves required.

#### Respiratory protection

Use in well-ventilated area ONLY. NOTICE: Reports have associated repeated and prolonged occupational over exposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. To avoid breathing vapor or spray mist open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air or wear an appropriate, properly fitted respirator (NIOSH approved), or leave the area. NOTE: Follow respirator manufacturer's instructions carefully for respirator use.

#### General hygiene considerations

Wash hands thoroughly after handling. Wash contaminated clothing before reuse.

## 9. Physical and Chemical Properties

**Information on basic physical and chemical properties**

<b>Physical State</b>	Aerosol	<b>Odor</b>	Petroleum distillates
<b>Appearance</b>	Dark yellow to light green liquid	<b>Odor threshold</b>	No information available
<b>Color</b>	dark yellow		
<b>Property</b>	<b>Values</b>	<b>Remarks • Method</b>	
<b>pH</b>	Not applicable	Solvent-based product.	
<b>Melting point/freezing point</b>	Not applicable	No information available	
<b>Boiling point/boiling range</b>	Acetone 133 F/56.29 C	No information available	
<b>Flash Point</b>	Not Available. This is an aerosol product for which Flame Projection is over 18 inches with 1 inches flashback. Temperatures above 120 F may cause cans to burst.	No information available	
<b>Evaporation Rate</b>	Faster than butyl acetate	No information available	
<b>Flammability (solid, gas)</b>		No information available	
<b>Flammability Limits in Air</b>		No information available	
<b>Upper flammability limits</b>	Not available		
<b>Lower Flammability Limit</b>	Not available		
<b>Vapor pressure</b>		No information available	
<b>Vapor Density</b>		No information available	
<b>Specific gravity</b>	0.910 +/- 0.015 concentrate	No information available	
<b>Water solubility</b>	Insoluble in water	No information available	
<b>Solubility in other solvents</b>		No information available	
<b>Partition coefficient</b>		No information available	
<b>Autoignition Temperature</b>		No information available	
<b>Decomposition temperature</b>		No information available	
<b>Kinematic viscosity</b>		No information available	
<b>Dynamic viscosity</b>		No information available	
<b>Explosive properties</b>	No information available		
<b>Oxidizing properties</b>	No information available		
<b>Other Information</b>			
<b>Softening point</b>	No information available		
<b>Molecular weight</b>	No information available		
<b>VOC content (%)</b>	49.85%		
<b>Density</b>	7.58 lb/gal		
<b>Bulk Density</b>	No information available		

**10. Stability and Reactivity**

**Reactivity**  
 Not applicable  
 no data available

**Chemical stability**  
 Stable.

**Possibility of hazardous reactions**  
 Temperatures above 130 °F may cause cans to burst with force.  
     **hazardous polymerization**      Hazardous polymerization does not occur.

**Conditions to Avoid**  
 Temperatures above 122 °F (50 °C).

**Incompatible Materials**  
 Avoid heat, open flame and contact with strong acids, strong bases and strong oxidizers.

**Hazardous decomposition products**  
 Thermal decomposition may yield gases like nitrogen oxides, carbon monoxide and carbon dioxide.

**11. Toxicological Information**

**FG 433-4105-8 SPRAYPAK VANDAL MARK REMOVER**

**Information on likely routes of exposure**

**Product Information** This product has not been tested as whole. See below for information on ingredients.

**inhalation** no data available.

**Eye Contact** no data available.

**Skin contact** no data available.

**INGESTION** no data available.

Chemical name	Oral LD50	dermal LD50	Inhalation LC50
Acetone 67-64-1	= 5800 mg/kg ( Rat )	-	= 50100 mg/m <sup>3</sup> ( Rat ) 8 h
Dimethyl Glutarate 1119-40-0	= 8191 mg/kg ( Rat )	-	> 5.6 mg/L ( Rat ) 4 h
Petroleum naphtha, light aromatic 64742-95-6	= 8400 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	= 3400 ppm ( Rat ) 4 h
Propane 74-98-6	-	-	= 658 mg/L ( Rat ) 4 h
Toluene 108-88-3	= 2600 mg/kg ( Rat )	= 12000 mg/kg ( Rabbit )	= 12.5 mg/L ( Rat ) 4 h
N-Butane 106-97-8	-	-	= 658 g/m <sup>3</sup> ( Rat ) 4 h
1,2,4 Trimethylbenzene 95-63-6	= 3280 mg/kg ( Rat )	> 3160 mg/kg ( Rabbit )	= 18 g/m <sup>3</sup> ( Rat ) 4 h
Propylene carbonate 108-32-7	= 29000 mg/kg ( Rat )	> 20 mL/kg ( Rabbit )	-
Ethyl alcohol 64-17-5	= 7060 mg/kg ( Rat )	-	= 124.7 mg/L ( Rat ) 4 h
Pine Oil 8002-09-3	= 3200 mg/kg ( Rat )	= 5 g/kg ( Rabbit )	-
D-Limonene 5989-27-5	= 4400 mg/kg ( Rat )	> 5 g/kg ( Rabbit )	-
Diacetone alcohol 123-42-2	= 4 g/kg ( Rat )	= 13500 mg/kg ( Rabbit )	-
Cocamide diethanolamine 68603-42-9	= 12400 µL/kg ( Rat )	-	-
Cumene 98-82-8	= 1400 mg/kg ( Rat )	= 12300 µL/kg ( Rabbit )	> 3577 ppm ( Rat ) 6 h = 39000 mg/m <sup>3</sup> ( Rat ) 4 h

**Information on toxicological effects**

**Symptoms** Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Skin corrosion/irritation** May cause skin irritation and reddening after prolonged or repeated contact with skin.

**Serious eye damage/eye irritation** Irritating to eyes.

**irritation** May cause skin and eye irritation.

**corrosivity** Not applicable.

**sensitization** No information available.

**Germ Cell Mutagenicity** No information available.

**carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen. Ethanol has been shown to be carcinogenic in long-term studies only when consumed as alcoholic beverage.

Chemical name	ACGIH	IARC	NTP	OSHA
Toluene 108-88-3		Group 3		
D-Limonene 5989-27-5		Group 2A Group 3		X

**FG 433-4105-8 SPRAYPAK VANDAL MARK REMOVER**

Cocamide diethanolamine 68603-42-9		Group 2B		X
Cumene 98-82-8		Group 2B		X

**Reproductive Toxicity** No information available.  
**STOT - single exposure** No information available.  
**STOT - repeated exposure** No information available.  
**Aspiration Hazard** No information available.

**Numerical measures of toxicity - Product Information**

**Unknown acute toxicity** -

The following values are calculated based on chapter 3.1 of the GHS document .

**ATEmix (oral)** 3025 mg/kg  
**ATEmix (dermal)** 3918 mg/kg  
**ATEmix (inhalation-gas)** 1395 mg/l  
**ATEmix (inhalation-dust/mist)** 3.7 mg/l  
**ATEmix (inhalation-vapor)** 13 mg/l

**12. Ecological Information**

This product contains chemicals which are listed as a marine pollutants according to DOT.

**ecotoxicity**

31.05% of the mixture consists of component(s) of unknown hazards to the aquatic environment

Chemical name	Algae/aquatic plants	Fish	Toxicity to Microorganisms	Crustacea
Acetone 67-64-1		6210 - 8120: 96 h Pimephales promelas mg/L LC50 static 4.74 - 6.33: 96 h Oncorhynchus mykiss mL/L LC50 8300: 96 h Lepomis macrochirus mg/L LC50	EC50 = 14500 mg/L 15 min	10294 - 17704: 48 h Daphnia magna mg/L EC50 Static 12600 - 12700: 48 h Daphnia magna mg/L EC50
Dimethyl Glutarate 1119-40-0		19.6 - 26.2: 96 h Pimephales promelas mg/L LC50 static		122.1 - 163.5: 48 h Daphnia magna mg/L EC50
Petroleum naphtha, light aromatic 64742-95-6		9.22: 96 h Oncorhynchus mykiss mg/L LC50		6.14: 48 h Daphnia magna mg/L EC50
Toluene 108-88-3	433: 96 h Pseudokirchneriella subcapitata mg/L EC50 12.5: 72 h Pseudokirchneriella subcapitata mg/L EC50 static	15.22 - 19.05: 96 h Pimephales promelas mg/L LC50 flow-through 12.6: 96 h Pimephales promelas mg/L LC50 static 5.89 - 7.81: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 54: 96 h Oryzias latipes mg/L LC50 static 11.0 - 15.0: 96 h Lepomis macrochirus mg/L LC50 static 28.2: 96 h Poecilia reticulata mg/L LC50 semi-static 50.87 - 70.34: 96 h Poecilia reticulata mg/L LC50 static 14.1 - 17.16: 96 h Oncorhynchus mykiss mg/L LC50 static 5.8: 96 h Oncorhynchus mykiss mg/L LC50 semi-static	EC50 = 19.7 mg/L 30 min	5.46 - 9.83: 48 h Daphnia magna mg/L EC50 Static 11.5: 48 h Daphnia magna mg/L EC50
1,2,4 Trimethylbenzene 95-63-6		7.19 - 8.28: 96 h Pimephales promelas mg/L LC50 flow-through		6.14: 48 h Daphnia magna mg/L EC50
Propylene carbonate 108-32-7	500: 72 h Desmodemus subspicatus mg/L EC50	1000: 96 h Cyprinus carpio mg/L LC50 semi-static 5300:	EC50 > 10000 mg/L 17 h	500: 48 h Daphnia magna mg/L EC50



**FG 433-4105-8 SPRAYPAK VANDAL MARK REMOVER**

		96 h Leuciscus idus mg/L LC50 static		
Ethyl alcohol 64-17-5		12.0 - 16.0: 96 h Oncorhynchus mykiss mL/L LC50 static 100: 96 h Pimephales promelas mg/L LC50 static 13400 - 15100: 96 h Pimephales promelas mg/L LC50 flow-through	EC50 = 34634 mg/L 30 min EC50 = 35470 mg/L 5 min	9268 - 14221: 48 h Daphnia magna mg/L LC50 2: 48 h Daphnia magna mg/L EC50 Static 10800: 24 h Daphnia magna mg/L EC50
Pine Oil 8002-09-3				17 - 28: 48 h Daphnia magna mg/L EC50 Flow through
D-Limonene 5989-27-5		0.619 - 0.796: 96 h Pimephales promelas mg/L LC50 flow-through 35: 96 h Oncorhynchus mykiss mg/L LC50		
Diacetone alcohol 123-42-2		420: 96 h Lepomis macrochirus mg/L LC50 static 420: 96 h Lepomis macrochirus mg/L LC50		8750: 24 h Daphnia magna mg/L EC50
Cocamide diethanolamine 68603-42-9		3.6: 96 h Brachydanio rerio mg/L LC50 semi-static		4.2: 24 h Daphnia magna mg/L EC50
Cumene 98-82-8	2.6: 72 h Pseudokirchneriella subcapitata mg/L EC50	6.04 - 6.61: 96 h Pimephales promelas mg/L LC50 flow-through 4.8: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 2.7: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 5.1: 96 h Poecilia reticulata mg/L LC50 semi-static	EC50 = 0.89 mg/L 5 min EC50 = 1.10 mg/L 15 min EC50 = 1.48 mg/L 30 min EC50 = 172 mg/L 24 h	0.6: 48 h Daphnia magna mg/L EC50 7.9 - 14.1: 48 h Daphnia magna mg/L EC50 Static

**Persistence and degradability**

No information available.

**Bioaccumulation**

No information available.

Chemical name	Partition coefficient
Acetone 67-64-1	-0.24
Propane 74-98-6	2.3
Toluene 108-88-3	2.65
N-Butane 106-97-8	2.89
1,2,4 Trimethylbenzene 95-63-6	3.63
Propylene carbonate 108-32-7	0.48
Ethyl alcohol 64-17-5	-0.32
Diacetone alcohol 123-42-2	1.03
Cumene 98-82-8	3.55

**Other adverse effects**

**Ozone**

No information available

This product does not contain CFCs or other ozone depleting substances. Federal regulations prohibit the use CFC propellants in aerosols.

**13. Disposal Considerations**

**Waste treatment methods**

**FG 433-4105-8 SPRAYPAK VANDAL MARK REMOVER**

**Disposal of wastes**

Dispose of in accordance with federal, state and local regulations.

**Contaminated packaging**

Pressurized container: Do not pierce or burn, even after use. Do not puncture or incinerate container. If empty: Place in trash or offer for recycling if available. If partly filled: Call your local solid waste agency for disposal instructions.

Chemical name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Acetone 67-64-1		Included in waste stream: F039		U002
Toluene 108-88-3	U220	Included in waste streams: F005, F024, F025, F039, K015, K036, K037, K149, K151		U220
Cumene 98-82-8				U055

Chemical name	RCRA - Halogenated Organic Compounds	RCRA - P Series Wastes	RCRA - F Series Wastes	RCRA - K Series Wastes
Toluene 108-88-3			Toxic waste waste number F025 Waste description: Condensed light ends, spent filters and filter aids, and spent desiccant wastes from the production of certain chlorinated aliphatic hydrocarbons, by free radical catalyzed processes. These chlorinated aliphatic hydrocarbons are those having carbon chain lengths ranging from one to and including five, with varying amounts and positions of chlorine substitution.	

Chemical name	California Hazardous Waste Status
Acetone 67-64-1	Ignitable
Toluene 108-88-3	Toxic Ignitable
Ethyl alcohol 64-17-5	Toxic Ignitable
D-Limonene 5989-27-5	Toxic
Cumene 98-82-8	Toxic Ignitable

**14. Transport Information**

**DOT**

**UN/ID no**  
**Proper Shipping Name**  
**Hazard Class**  
**Marine pollutant**

Limited Quantity - Graffiti Remover  
UN1950  
Limited quantity (LQ)  
2.1  
This product contains chemicals which are listed as a marine pollutants according to DOT.

**15. Regulatory information**

**International Inventories**

**TSCA**

All ingredients of this product are listed or are excluded from listing under the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

**DSL**

All ingredients are listed or are excluded from listing on the DSL.

**Legend:**

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

**US Federal Regulations**

**SARA 313**

This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know Act of 1986 and 40 CFR 372. This information must be included in all SDSs that are copied and distributed for this material.

Chemical name	CAS No	weight-%	SARA 313 - Threshold Values %
Toluene - 108-88-3	108-88-3	5-10	1.0
1,2,4 Trimethylbenzene - 95-63-6	95-63-6	5-10	1.0
Cumene - 98-82-8	98-82-8	<1	1.0

**SARA 311/312 Hazard Categories**

<b>Acute Health Hazard</b>	yes
<b>Chronic Health Hazard</b>	yes
<b>Fire Hazard</b>	yes
<b>Sudden release of pressure hazard</b>	No
<b>Reactive Hazard</b>	No

**CWA (Clean Water Act)**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Toluene 108-88-3	1000 lb	X	X	X

**CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Acetone 67-64-1	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
Toluene 108-88-3	1 lb		RQ 1 lb final RQ RQ 0.454 kg final RQ
Cumene 98-82-8	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

**US State Regulations**

**California Proposition 65**

This product contains the following Proposition 65 chemicals.

Chemical name	California Proposition 65
Toluene - 108-88-3	Developmental Female Reproductive
Cocamide diethanolamine - 68603-42-9	Carcinogen
Cumene - 98-82-8	Carcinogen

**U.S. State Right-to-Know Regulations**

Chemical name	New Jersey	Massachusetts	Pennsylvania
Acetone 67-64-1	X	X	X

**FG 433-4105-8 SPRAYPAK VANDAL MARK REMOVER**

Propane 74-98-6	X	X	X
Toluene 108-88-3	X	X	X
N-Butane 106-97-8	X	X	X
1,2,4 Trimethylbenzene 95-63-6	X	X	X
Ethyl alcohol 64-17-5	X	X	X
Pine Oil 8002-09-3	X		
Diacetone alcohol 123-42-2	X	X	X
Cumene 98-82-8	X	X	X

**U.S. EPA Label information**

**EPA Pesticide registration number** Not applicable

**16. Other information**

<b>NFPA</b>	<b>Health Hazards</b> 2	<b>Flammability</b> 4	<b>Instability</b> 1	<b>Physical and chemical properties</b> Not applicable
<b>HMIS</b>	<b>Health Hazards</b> 2*	<b>Flammability</b> 4	<b>Physical Hazards</b> 1	<b>Personal Protection</b> X

**Prepared by** Regulatory Department  
**Issue date** 12-Mar-2015  
**Revision note**  
 This SDS supercedes a previous MSDS dated: Sept. 10, 2013

**Disclaimer**

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**